



TruBend Series 8000

Technical data

**TruBend 8230
(bending length 4420 mm)**

**TruBend 8320
(bending length 3230 mm)**

**TruBend 8320
(bending length 6120 mm)**

PRESS FORCE	2300 kN	3200 kN	3200 kN
BENDING LENGTH	4420 mm	3230 mm	6120 mm
WIDTH BETWEEN COLUMNS	3680 mm	2510 mm	5090 mm
MAX. DISTANCE FROM PRESS BEAM TO TABLE	-	1000 mm	-
USABLE OPEN HEIGHT	880 mm	880 mm	880 mm
THROAT DEPTH	620 mm	620 mm	620 mm
USER INTERFACE	T-8000 S Multi-Touch Control	T-8000 S Multi-Touch Control	T-8000 S Multi-Touch Control
MAXIMUM SPEED Y AXIS, OPERATION	10 mm/s	10 mm/s	10 mm/s
DIMENSIONS, WEIGHTS			
LENGTH	5318 mm	4188 mm	7090 mm
WIDTH	2830 mm	2830 mm	2830 mm
HEIGHT	3970 mm	3970 mm	3970 mm
WEIGHT	25000 kg	26000 kg	40000 kg

**TruBend 8400
(bending length 4420 mm)**

**TruBend 8400
(bending length 6120 mm)**

**TruBend 8600
(bending length 4420 mm)**

PRESS FORCE	4000 kN	4000 kN	6000 kN
BENDING LENGTH	4420 mm	6120 mm	4420 mm
WIDTH BETWEEN COLUMNS	3680 mm	5090 mm	3680 mm
MAX. DISTANCE FROM PRESS BEAM TO TABLE	1000 mm	-	1000 mm
USABLE OPEN HEIGHT	880 mm	880 mm	880 mm
THROAT DEPTH	620 mm	620 mm	620 mm
USER INTERFACE	T-8000 S Multi-Touch Control	T-8000 S Multi-Touch Control	T-8000 S Multi-Touch Control
MAXIMUM SPEED Y AXIS, OPERATION	10 mm/s	10 mm/s	10 mm/s
DIMENSIONS, WEIGHTS			
LENGTH	5398 mm	7103 mm	5458 mm
WIDTH	2830 mm	2830 mm	2830 mm
HEIGHT	3970 mm	3970 mm	3970 mm
WEIGHT	34000 kg	45000 kg	45000 kg

**TruBend 8600
(bending length 6120 mm)**

**TruBend 8800
(bending length 6120 mm)**

**TruBend 8800
(bending length 7050 mm)**

PRESS FORCE	6000 kN	8000 kN	8000 kN
BENDING LENGTH	6120 mm	6120 mm	7050 mm
WIDTH BETWEEN COLUMNS	5090 mm	5100 mm	6050 mm
MAX. DISTANCE FROM PRESS BEAM TO TABLE	1000 mm	-	-
USABLE OPEN HEIGHT	880 mm	675 mm ¹	675 mm ¹
THROAT DEPTH	620 mm	420 mm ¹	420 mm ¹
USER INTERFACE	T-8000 S Multi-Touch Control	T-8000 S Multi-Touch Control	T-8000 S Multi-Touch Control
MAXIMUM SPEED Y AXIS, OPERATION	10 mm/s	10 mm/s	10 mm/s
DIMENSIONS, WEIGHTS			
LENGTH	7165 mm	7180 mm	8150 mm
WIDTH	2880 mm	2980 mm ²	2980 mm ²
HEIGHT	3995 mm	4570 mm ²	4570 mm ²
WEIGHT	51000 kg	70000 kg	74000 kg ²

**TruBend 8800
(bending length 8050 mm)**

**TruBend 81000
(bending length 7050 mm)**

**TruBend 81000
(bending length 8050 mm)**

PRESS FORCE	8000 kN	10000 kN	10000 kN
BENDING LENGTH	8050 mm	7050 mm	8050 mm
WIDTH BETWEEN COLUMNS	7050 mm	6050 mm	7050 mm
MAX. DISTANCE FROM PRESS BEAM TO TABLE	-	-	-
USABLE OPEN HEIGHT	675 mm ¹	675 mm ¹	675 mm ¹
THROAT DEPTH	420 mm ¹	420 mm ¹	420 mm ¹
USER INTERFACE	T-8000 S Multi-Touch Control	T-8000 S Multi-Touch Control	T-8000 S Multi-Touch Control
MAXIMUM SPEED Y AXIS, OPERATION	10 mm/s	8 mm/s	8 mm/s
DIMENSIONS, WEIGHTS			
LENGTH	9150 mm	8150 mm	9150 mm
WIDTH	2980 mm ²	2980 mm ²	2980 mm ²
HEIGHT	4770 mm ²	4750 mm ²	4750 mm ²
WEIGHT	82000 kg ²	93000 kg ²	98000 kg ²

Footnotes

1 — durch Option vergrößerbar

2 — können mit Optionen abweichen