



# TruTool TKF 1500 with 2-gear gearbox

Technical data

**TruTool TKF 1500 with 2-speed gearbox, 1st gear****TruTool TKF 1500 with 2-speed gearbox, 2nd gear****MAXIMUM CHAMFER LENGTHS / MAXIMUM CHAMFER HEIGHTS**

Maximum chamfer length, steel 400 N/mm <sup>2</sup>	15 mm	15 mm
Maximum chamfer height, steel 400 N/mm <sup>2</sup>	10.6 mm	10.6 mm
Maximum chamfer length, steel 600 N/mm <sup>2</sup>	11 mm	9 mm
Maximum chamfer height, steel 600 N/mm <sup>2</sup>	7.8 mm	6.4 mm
Maximum chamfer length, steel 800 N/mm <sup>2</sup>	9 mm	6 mm
Maximum chamfer height, steel 800 N/mm <sup>2</sup>	6.4 mm	4.2 mm

**RADII**

Smallest radius	55 mm	55 mm
-----------------	-------	-------

**GENERAL**

Working speed (max.)	1.25 m/min	2 m/min
Nominal power consumption	2600 W	2600 W
Sheet thickness	4 mm - 160 mm	4 mm - 160 mm

**DIMENSIONS**

Length	607 mm	607 mm
Height	361 mm	361 mm

**WEIGHT**

Weight	19.5 kg	19.5 kg
--------	---------	---------